

The listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A **computer implemented** method for controlling or monitoring a target software component of an isolated execution unit, the method comprising:
  - introducing an intermediary software component within an isolated execution unit;
  - indicating an identifier of a target software component to the intermediary software component;
  - starting the target software component having the indicated identifier within the isolated execution unit; and
  - establishing a communication path between the intermediary software component and an external program that is outside of the isolated execution unit whereby the external program can control or monitor the target software component via the established communication path.
2. (Currently Amended) A **computer implemented** method as recited in claim 1, wherein the established communication path uses an inter isolation communication protocol.
3. (Currently Amended) A **computer implemented** method as recited in claim 2, where the inter isolation communication protocol is a remote method invocation technique.
4. (Currently Amended) A **computer implemented** method as recited in claim 1, wherein the communication path is established by the intermediary software component.

5. (Currently Amended) A **computer implemented** method as recited in claim 1, further comprising, **prior to establishing the communication path**, initializing the isolated execution unit **into a desired state supplied by the external program**.
6. (Currently Amended) A **computer implemented** method as recited in claim 5, wherein the isolated execution unit is initialized **into the desired state, supplied by the external program**, by the intermediary software component.
7. (Currently Amended) A **computer implemented** method as recited in claim 6, further comprising indicating one or more parameters **representing the desired state** for initializing the isolated execution unit, wherein the initialization of the isolated execution unit is based on the indicated one or more parameters.
8. (Currently Amended) A **computer implemented** method as recited in claim 7, wherein the external program indicates the one or more parameters.
9. (Currently Amended) A **computer implemented** method as recited in claim 1, further comprising:
- indicating an execution control parameter to the intermediary software component; and
- invoking the indicated execution control parameter on the target software component
- using an application programming interface (API) of the target software component.
10. (Currently Amended) A **computer implemented** method as recited in claim 9, wherein the execution control parameter is a request that has a first format of an inter isolation

communication protocol, the method further comprising translating the first format into a second format that is acceptable by the API of the target software component.

11. (Currently Amended) A **computer implemented** method as recited in claim 10, wherein the intermediary software component performs the translation.

12. (Currently Amended) A **computer implemented** method as recited in claim 9, further comprising:

receiving a result at the intermediary software component from the target component in response to the invoked execution control parameter; and

sending the result to the external program.

13. (Currently Amended) A **computer implemented** method as recited in claim 12, wherein the intermediary software component sends the result.

14. (Currently Amended) A **computer implemented** method as recited in claim 13, wherein the result has a first format that is acceptable by the API of the target software component, the method further comprising translating the first format into a second format that is an inter isolation communication protocol before sending the result to the external program.

15. (Currently Amended) A **computer implemented** method as recited in claim 1, wherein the identifier of the target software component is provided by the external program.

16. (original) A computer readable medium containing instructions for controlling or monitoring a target software component of an isolated execution unit, the computer readable medium comprising:

computer code for introducing an intermediary software component within an isolated execution unit;

computer code for indicating an identifier of a target software component to the intermediary software component;

computer code for starting the target software component having the indicated identifier within the isolated execution unit; and

computer code for establishing a communication path between the intermediary software component and an external program that is outside of the isolated execution unit whereby the external program can control or monitor the target software component via the established communication path.

17. (original) A computer readable medium as recited in claim 16, wherein the established communication path uses an inter isolation communication protocol.

18. (original) A computer readable medium as recited in claim 17, where the inter isolation communication protocol is a remote method invocation technique.

19. (original) A computer readable medium as recited in claim 16, wherein the communication path is established by the intermediary software component.

20. (Currently Amended) A computer readable medium as recited in claim 16, further comprising computer code for, **prior to establishing the communication path,** initializing the isolated execution unit **into a desired state supplied by the external program.**
21. (Currently Amended) A computer readable medium as recited in claim 20, wherein the isolated execution unit is initialized **into a desired state supplied by the external program** by the intermediary software component.
22. (Currently Amended) A computer readable medium as recited in claim 21, further comprising computer code for indicating one or more parameters **representing the desired state** for initializing the isolated execution unit, wherein the initialization of the isolated execution unit is based on the indicated one or more parameters.
23. (original) A computer readable medium as recited in claim 22, wherein the external program indicates the one or more parameters.
24. (original) A computer readable medium as recited in claim 16, further comprising:  
computer code for indicating an execution control parameter to the intermediary software component; and  
computer code for invoking the indicated execution control parameter on the target software component using an application programming interface (API) of the target software component.
25. (original) A computer readable medium as recited in claim 24, wherein the execution control parameter is a request that has a first format of an inter isolation communication protocol,

the computer readable medium further comprising computer code for translating the first format into a second format that is acceptable by the API of the target software component.

26. (original) A computer readable medium as recited in claim 25, wherein the intermediary software component performs the translation.

27. (original) A computer readable medium as recited in claim 24, further comprising:  
computer code for receiving a result at the intermediary software component from the target component in response to the invoked execution control parameter; and  
computer code for sending the result to the external program.

28. (original) A computer readable medium as recited in claim 27, wherein the intermediary software component sends the result.

29. (original) A computer readable medium as recited in claim 28, wherein the result has a first format that is acceptable by the API of the target software component, the computer readable medium further comprising computer code for translating the first format into a second format that is an inter isolation communication protocol before sending the result to the external program.

30. (original) A computer readable medium as recited in claim 16, wherein the identifier of the target software component is provided by the external program.

31. (original) A computer implemented system operable to control or monitor a target software component of an isolated execution unit, comprising:

an isolated execution unit;  
an intermediary software component within the isolated execution unit; and  
an external program that is outside of the isolated execution unit, the external program being configured to indicate an identifier of a target software component to the intermediary software component,

wherein the intermediary software component is configured to start the target software component having the indicated identifier within the isolated execution unit and establish a communication path between the intermediary software component and the external program whereby the external program can control or monitor the target software component via the established communication path.

32. (original) A computer implemented system as recited in claim 31, wherein the established communication path uses an inter isolation communication protocol.

33. (original) A computer implemented system as recited in claim 32, where the inter isolation communication protocol is a remote method invocation technique.

34. (Currently Amended) A computer implemented system as recited in claim 31, wherein the intermediary software component is further configured to, **prior to establishing the communication path,** initialize the isolated execution unit **into a desired state supplied by the external program.**

35. (Currently Amended) A computer implemented system as recited in claim 34, wherein the external program is further configured to indicate one or more parameters **representing the desired state** for initializing the isolated execution unit to the intermediary software component,

wherein the initialization of the isolated execution unit is based on the indicated one or more parameters.

36. (original) A computer implemented system as recited in claim 31, wherein the external program is further configured to indicate an execution control parameter to the intermediary software component and the intermediary software component is further configured to invoke the indicated execution control parameter on the target software component using an application programming interface (API) of the target software component.

37. (original) A computer implemented system as recited in claim 36, wherein the execution control parameter is a request has a first format that is an inter isolation communication protocol, the intermediary software component being further configured to translate the first format into a second format that is acceptable by the API of the target software component.

38. (original) A computer implemented system as recited in claim 36, wherein the intermediary software component is further configured to receive a result at the intermediary software component from the target component in response to the invoked execution control parameter and send the result to the external program.

39. (Currently Amended) A computer implemented system as recited in claim ~~[[12]]~~ 38, wherein the result has a first format that is acceptable by the API of the target software component, the intermediary software component being further configured to translate the first format into a second format that is an inter isolation communication protocol before sending the result to the external program.